Quassel IRC - Feature #1181

Add SASL EXTERNAL

08/26/2012 11:06 PM - Anonymous

Status:	Resolved	Start date:	08/26/2012	
Priority:	Normal	Due date:		
Assignee:		% Done:	0%	
Category:	Quassel Core	Estimated time:	0.00 hour	
Target version:	0.9.0			
OS:	Any			

Description

When CertFP is used as authentication mechanism, there is still a race condition. SASL EXTERNAL will, just like regular SASL, make the client authenticated during the connection registration.

In the Auto Identify settings, another checkbox should be added (only enabled when a certicate has been added to the identity used for this network), which would enable SASL EXTERNAL, then during the connection registration, after the sasl cap has been ack'ed, 'AUTHENTICATE EXTERNAL' should be sent.

For starters SASL PLAIN and EXTERNAL can be mutually exclusive, but ideally PLAIN would be used as fallback should EXTERNAL fail.

History

#1 - 09/26/2012 02:41 PM - Anonymous

- Assignee set to Anonymous
- Target version set to Some future release

Implemented in MR 149

#2 - 02/20/2013 07:45 PM - Anonymous

- Status changed from New to Resolved
- Target version changed from Some future release to 0.9.0

Merged in af5909677a97f62b20d89229be42701762ae05c3