

Quassel IRC - Bug #1305

When connected to irssiproxy, quassel reports messages sent from irssi in the wrong buffer/window/

08/07/2014 08:35 PM - Caesar

Status:	New	Start date:	08/07/2014
Priority:	Low	Due date:	
Assignee:		% Done:	0%
Category:	Quassel Core	Estimated time:	0.00 hour
Target version:		OS:	Linux
Version:	0.11-pre		
Description I have set up irssi to listen as proxy. In that mode, it acts a bit like a bouncer. I connected quasselcore to that. (I know, that is a bit strange, but whatever.) When I send a message from irssi to user test, in a query, the following message is forwarded to quassel: :JCaesar!julius@proxy PRIVMSG test :testmsg Quassel interprets that as message from someone with my own nick and opens a new query window with my nick on it instead of putting it into the query for "test". I have patched my quassel to stop doing that, so I don't care whether it is fixed. I just wanted to report it and drop the diff: <pre>diff --git a/src/core/ircparser.cpp b/src/core/ircparser.cpp index acc765a..5cf0c26 100644 --- a/src/core/ircparser.cpp +++ b/src/core/ircparser.cpp @ -189,6 +189,12 @ void IrcParser::processNetworkIncoming(NetworkDataEvent *e) msg = decrypt(net, target, msg); + // When quassel is behind a proxy, a message may appear with our nick as sender. + // Work that around + if (net->myNick() == senderNick) { + target = params⁰; + } + events << new IrcEventRawMessage(EventManager::IrcEventRawPrivmsg, net, msg, prefix, target, e->timestamp()); }</pre>			