

Quassel IRC - Bug #52

Sync Bufferswitches via QDataWidgetMapper

07/10/2007 01:54 PM - EgS

| | | | |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|------------------------|-----------|
| Status: | Closed | Start date: | |
| Priority: | High | Due date: | |
| Assignee: | EgS | % Done: | 0% |
| Category: | Quassel Client | Estimated time: | 0.00 hour |
| Target version: | 0.2.0-alpha1 | OS: | Any |
| Version: | 0.13.1 | | |
| Description | | | |
| Currently bufferswitches are handled somewhat crude. I just learned about QDataWidgetMapper, wich allows to map different data of an AbstractModel to Widgets. Since the buffers are already wrapped into a BufferModel this facility should allow us to sync the bufferswitches somewhat automagically. Syncing applies to: - topic - input line - chatwidget (obviously) - nicklist | | | |

History

#1 - 11/04/2007 02:38 PM - EgS

Ok QDataWidgetmapper basically sucks. At least for what I had in mind to do with it.

Wrote my own Class to take care of this now: ModelPropertyMapper:

it can be easily used to map a specific column of a model to a property of qobject using a specific Role:

for example the following line maps the DisplayRole of Column 0 to the "topic" property of the topic widget:

```
Client::bufferModel()->mapProperty(0, Qt::DisplayRole, topicwidget, "topic");
```

-> close