

Quassel IRC - Bug #958

PostgreSQL Syntax Errors

05/02/2010 10:09 PM - titanofold

Status:	Resolved	Start date:	05/02/2010
Priority:	Normal	Due date:	
Assignee:		% Done:	100%
Category:	Quassel Core	Estimated time:	0.00 hour
Target version:		OS:	Any
Version:	0.6-pre		
Description			
<p>When using PostgreSQL as the backend to Quassel Core, my logs are filled with syntax errors. The errors stem from duplicate keys and null values for senderid. Quassel Core should not depend on PgSQL to prevent duplicate entries -- in other words, Quassel Core should check for an existing entry -- and it shouldn't try to submit null values for a column that has a NOT NULL constraint.</p> <p>I've attached a file that shows the entries that PgSQL receiving. I've limited it to just 20, but after less than a week of using Quassel, I have 70,938 entries in my log regarding it.</p>			

Associated revisions

Revision c371e27b - 02/19/2013 10:30 PM - debfx

Check if user setting pair exists before inserting/updating it.

If it exists it's inserted else the date is updated.

This fixes a (harmless) error that clutters the postgres log.

Fixes #958

History

#1 - 10/06/2010 05:45 PM - ddenis

I have a similar issue with "senderid" errors appearing on the log:

2010-10-06 19:28:04 Warning: PostgreSqlStorage::executePreparedQuery() no prepared Query with handle "insert_sender" on Database

"quassel_QPSQL_con_3"

2010-10-06 19:28:04 Error: unhandled Error in QSqlQuery!

2010-10-06 19:28:04 Error: last Query: EXECUTE quassel_3 ('2010-10-6 17:28:04.357', 10, 2, 4, 'asimov.freenode.net', '*** Looking up your hostname...')

2010-10-06 19:28:04 Error: executed Query:

2010-10-06 19:28:04 Error: bound Values:

2010-10-06 19:28:04 Error: Error Number: -1

2010-10-06 19:28:04 Error: Error Message: ERROR: null value in column "senderid" violates not-null constraintQPSQL: Unable to create query

2010-10-06 19:28:04 Error: Driver Message: QPSQL: Unable to create query

2010-10-06 19:28:04 Error: DB Message: ERROR: null value in column "senderid" violates not-null constraint

#2 - 10/06/2011 12:06 AM - jotik

I'm getting same error and they fill up system logs quite quickly. Any progress on fixing this?

#3 - 10/06/2011 12:08 AM - jotik

I still get errors like

```
Oct 6 00:59:54 localhost postgres[29692]: [917-1] ERROR: duplicate key value violates unique constraint "user_setting_pkey"
```

```
Oct 6 00:59:54 localhost postgres[29692]: [917-2] DETAIL: Key (userid, settingname)=(1, BufferViews) already exists.
```

and

```
Oct 6 00:59:54 localhost postgres[29692]: [918-1] ERROR: duplicate key value violates unique constraint "user_setting_pkey"
```

```
Oct 6 00:59:54 localhost postgres[29692]: [918-2] DETAIL: Key (userid, settingname)=(1, GlobalNetworkConfig) already exists.
```

with Quassel 0.7.3.

#4 - 10/18/2011 08:44 PM - dazjorz

Same here, but possibly a new issue / regression, because it happens for me since the upgrade from 0.7.1 to 0.7.3.

#5 - 02/19/2013 10:39 PM - debfx

- *Status changed from New to Resolved*

- *% Done changed from 0 to 100*

Applied in changeset quassel|commit:c371e27b23667e05cccffb200acfb35f5af2a64a.

Files

results.txt	9.36 KB	05/02/2010	titanofold
-------------	---------	------------	------------